

**INDUSTRIAL DIESEL ENGINE** 

## **KUBOTA 05 SERIES (3-cylinder)**


# D1305-E3B






### **RATED POWER**

## 21.7kW@3000rpm



Photographs may show non-standard equipment.

#### PERFORMANCE CURVE



#### FEATURES and BENEFITS

#### **EMISII**

Motorul D1305 cu aspiratie naturala (3600rpm) respecta reglementarile EPA Interim Tler 4 care sunt valabile pana in 2012. Acest motor respecta de asemenea standardele EU Stage IIA pe piata europeana.

#### **PUTERE**

Acesta este un motor de mare putere care are cea mai mare iesire, cu aspiratie naturala, in 3 cilindri din seria Kubota 05.

Pasajul de racire dintre cilindru, foloseste tehnologia Kubota si contra-masuri impotriva supraincalzirii, pentru rezistenta si fiabilitate.

#### **CURAT SI SILENTIOS**

Sistemul E-TVCS a fost imbunatatit. Fluxul de aer, camera de combustie si pistonii sunt imbunatatiti sa ofere cu 50% mai putin PM (particule in suspensie).

#### **OPTIUNE**

Exista o varietate mare de optiuni suplimentare pentru motoarele din Seria 05.


D1305-E3B **KUBOTA 05 SERIES** 


#### **GENERAL SPECIFICATION**

Model		D1305-E3B
Emission Regulation		Interim Tier 4 / Stage <b>I</b> II A
Туре		Vertical 4-cycle Liquid Cooled Diesel
Number of Cylinders		3
Bore	mm (in)	78.0 (3.07)
Stroke	mm (in)	88.0 (3.46)
Displacement	L (cu.in)	1.261 (76.95)
Combustion System		IDI
Intake System		Naturally Aspirated
Maximum Speed	rpm	3000
Output: Gross Intermittent	kW	21.7
	hp	29.1
	ps	29.5
Direction of Rotation		Counterclockwise Viewed on Flywheel
Oil Pan Capacity	L (gal)	5.7 (1.51)
Starter Capacity	V-kW	12-1.2 [US] / 12-1.4 [EU]
Alternator Capacity	V-A	12-40
Length	mm (in)	497.6 (19.59)
Width	mm (in)	396.0 (15.59)
Height (1)	mm (in)	590.1 (23.20)
Height (2)	mm (in)	215.6 (8.49)
Dry Weight	kg (lb)	95.0 (209.4)

<sup>\*</sup>Specification is subject to change without notice.

#### **DIMENSIONS**







Your Driving Force KUBOTA ENGINE

# **Mecanexim Engineering**

Str. Tudor Arghezi, nr.1, Comuna 1 Decembrie, judetul Ilfov Telefon: +40 744 671 621

http://kubota.com.ro http://mexanexim.ro

<sup>\*</sup>Output: Gross Intermittent SAE J1995

<sup>\*</sup>Dry weight is according to Kubota's standard specification. When specification varies, the weight will vary accordingly.